

cfm corporation fireplace br 36

Majestic Fireplaces® BR/BC Series

Installing Line For Gas Log

CFM Corporation fireplaces are designed to accept a 1/2 inch gas line for installation of an approved gas appliance. (CFM Corporation manufactures a wide variety of gas logs for use in CFM Corporation fireplaces.) Be sure to have the appliance installed in accordance with building codes.

Gas connection may enter from either left or right side of the fireplace.

Locate appropriate gas line in the outer casing of fireplace and remove insulation from gas line tube. (Fig. 27) From inside the fireplace, locate the knockout on the firebrick – be sure you are on the appropriate or "gas line" side of the fireplace. Using a flat bladed screwdriver or small chisel and hammer, carefully tap around the knockout until it loosens and falls out.

Install 1/2 inch certified gas pipe through opening. After gas pipe installation is complete, use insulation that was removed from gas line tube to repack space around the pipe. Material should be inserted from outside of the fireplace and packed tightly to totally seal between the pipe and tube.

Note: Gas pipe should not come in contact with any wood structures until it has reached a point at least one (1) inch away from fireplace side.

NOTE: When installing an ANSI Z21.11.2 ventless appliance, the finishing material used for the mantel must be rated at 250°F or greater.

BTU input of a gas appliance installed in fireplace should be rated less than 100,000 BTU/hr. Gas pipe installation is intended for connection to a decorative gas appliance only when (1) incorporating an automatic shutoff device and (2) complying with the Standard for Decorative Gas Appliances for Installation in Vented Fireplaces (ANSI Z21.60) or CSA draft requirements for Gas-Fired Log Lighters for Woodburning Fireplaces (Draft No. 4, August 1993).

Decorative gas appliance should be installed in accordance with the National Fuel Gas Code, ANSI Z223.1/NFPA 54 (latest edition).




Fig. 27 Gas line access.

CAUTION: WHEN USING DECORATIVE GAS APPLIANCE, FLUE DAMPER MUST BE SET IN FULLY OPEN POSITION. IF YOU HAVE GLASS DOORS ON THE FIREPLACE, THEY MUST ALSO BE FULLY OPENED.

WARNING: DO NOT OPERATE AN UNVENTED GAS LOG SET IN THIS FIREPLACE WITH THE CHIMNEY REMOVED.

WARNING: WHEN INSTALLING AN UNVENTED GAS LOG SET, THE CFM CORPORATION MODEL AH3244BK OR AH3244PB 4" ADJUSTABLE HOOD MUST BE USED.

Only unvented gas log sets which have been found to comply with the Standard for Unvented Room Heaters, ANSI Z21.11.2, are to be installed in this fireplace.

18

7412944

and Operating Manual. For Models: BR BR BC BC 4/07 Rev. Precautions CFM Corporation ?replaces and component parts have been .Vermont Casting BR36 EN User Manual Hearth installation, Minimum wall clearances, Minimum opening must be protected with CFM Corporation Wall.Need to fix your BR36 (Series BR/BC) Woodburning Fireplace? We have parts, diagrams, accessories and repair advice to make your tool repairs easy.Appliances BR36 - Majestic Operating Manual Woodburning Fireplace BR36 ?replaceopening must be protected with CFM Corporation WallShield Model.Superior BR Replacement Parts and Accessories. Superior BR / BR 2. Standard Series - 36" Radiant Wood Burning Fireplace.We have a CFM Corporation / MHSC / Lennox Hearth Products - Royalton fireplace M# BR36, s# FA40RH, we have never used in 3 years from .Firebrick Panels for a Majestic Fireplace BR36 BR36I BC36 BC36R Replacement Firebrick/Refractory.Need some information on your Majestic fireplace or stove? Find your products user guide and manuals here.Fits BR36, BC36, BE36, SR36, SC36, GBR36, NVBR36 (Note: Does Not Fit SR36A or SC36A); Please Do Not Order Pathline Products 36" Fireplace Doors For Majestic (CFM) Fireplace Manufacturer, Burgess Manufacturing Corporation.CFM Corporation - All rights reserved. Majestic Nothing can beat the Royalton BR/BC Wood Fireplace from Royalton BR36 Wood Burning Fireplace .4 panels make up the fireplace glass door set. Fits Majestic Brand fireplace units: BR36, BC36, SR36, SC36, GBR36, NVBR36, NVBC36 Burgess Manufacturing Corporation does not and shall not assume any liability whatsoever for use.Installation manual CFM Corporation WMC36 WMC42 Indoor Fireplace User .. BR/BC 9/29/97 Lift the ?replace front slightly and slide the metal safety strips.Precautions CFM Corporation ?replaces and component parts have been highly tested SR36A / SR42A SC36A / SC42A Listed UL / ULC-S Standard for . FP BR/BC Combo of IWF AND IWF 11/10/97 5 SR/SC.Only use CFM Corporation components or the warranty will be voided and a fire TL36 Series Woodburning Fireplace Circulating Model. " (16mm).Majestic Fireplaces is a registered trademark of CFM Corporation. Shown on Cover: MO18M Gas Logs shown with Royalton BR36 Wood Burning Fireplace.The BR36/42 (Builder Radiant) is a clean-face. ?replace and the BC36/42 (Builder Circulating) unit has. ?xed grilles. Precautions. CFM Corporation ?replaces.Country Stoves, Inc./ Lennox Hearth. Products. Striker S and 36 Elite. 11., C. Fireplace Xtrodinair (FPX) by Travis. Industries, Inc. . Brenden BR 11, 11., C. Vermont Castings/ CFM Corporation.